

TOP SPEED 4T SAE 10W/30 JASO MA2

Modern synthetic high-performance engine oil for 4-stroke motorcycles

Description

Modern synthetic high-performance engine oil for 4-stroke motorcycles. With this MC (Molecular Converted) technology high-quality base oils are refined chemically and and achieve a very high level of performance. JASO MA 2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Advantages

- Synthetic Performance
- excellent wear protection
- · particularly good thermal and shear stability
- reduces oil consumption
- ideal for wet multi-disc clutches (JASO MA2 approval)

Field of application

Available in four viscosities, MOTOREX TOP SPEED 4T oil has been especially developed for use in all motorcycles with medium to large engines, where a fully synthetic oil has not been expressly specified by the manufacturers. Ideal for motorcycles with wet multi-disc clutches. Also meets the highest demand of the manufacturer's.

Specifications

JASO MA2; API SN; API SM; API SL



JASO T 903 : 2016 PERFORMANCE IS GUARANTEED by MOTOREX AG

Technical data

<u>Properties</u>	Unit	Test according to	Values	
Colour			brown	
Density at 20 °C	g/cm³	ASTM D4052	0.852	
Viscosity at 40 °C	mm²/s	DIN 51562-1	74.1	
Viscosity at 100 °C		DIN 51562-1	11.1	
Viscosity index		DIN ISO 2909	141	
Viscosity according to HTHS at 150 °C	mPa⋅s	CEC-L-36 A-97	≥2.9	
Pourpoint	°C	ASTM D5950	-36	
Flash point C.O.C.	°C	DIN EN ISO 2592	>200	
CCS at	°C / mPa·s	ASTM D 5293	-25 / 5865	
Sulphate residue content	%	DIN EN ISO 6245	0.7	
NOACK	%	CEC L-40-A-93	8.3	
TBN	mg KOH/g	DIN ISO 3771	6.2	

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.



MOTOREX AG Bern-Zürich-Strasse 31 CH-4901 Langenthal Tel. +41 (0)62 919 75 75 info@motorex.com, www.motorex.com