

Printing date 04/12/2016

Reviewed on 04/12/2016

1 Identification

- · Product identifier
- · Trade name: RACING PRO 4T SAE 15W/50
- · Application of the substance / the mixture Only for proper handling. Engine oil
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

BUCHER AG LANGENTHAL MOTOREX-Schmiertechnik Bern–Zürich–Strasse 31 CH-4901_Langenthal_ Telefon_+41_(0)62_919_75_75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota

Phone: 001 763 417 1357

- · Information department: msds@motorex.com
- · Emergency telephone number: Toxicological Information Centre CH-8028 Zurich info@toxi.ch

T. +41 (0)44 251 51 51

USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child. Repr. 2



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

H402 Harmful to aquatic life. Aquatic Acute 3

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

· Signal word Warning

· Hazard-determining components of labeling:

Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts

· Hazard statements

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray P261

P280 Wear protective gloves.

P273 Avoid release to the environment.

P272 Contaminated work clothing must not be allowed out of the workplace.

Obtain special instructions before use. P201

P202 Do not handle until all safety precautions have been read and understood.

P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 1Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 112-41-4	dodec-1-ene	50-70%
	Flam. Liq. 4, H227	
	Distillates (petroleum), hydrotreated heavy	5-10%
Reg.nr.: 01-2119484627-25	paraffinic	
	Asp. Tox. 1, H304	

(Contd. on page 3)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

	(Co	ontd. of page 2)
CAS: 84605-29-8 Reg.nr.: 01-2119493626-26	Phosphorodithioic acid, mixed 0,0-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts	1-2.5%
	Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Aquatic Acute 2, H401	
CAS: 70024-69-0 Reg.nr.: 01-2119492616-28	Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts	0.25-1%
	Skin Sens. 1, H317	
CAS: 121158-58-5	p-Dodecylphenol	0.1-0.25%
Reg.nr.: 01-2119513207-49	Repr. 2, H361; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove residues with soap and water.

Remove contaminated clothing immediately.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

Consult a physician if irritation develops.

· After swallowing:

Do not induce vomitting. Do not take in resorption stimulating agents.

Consult a physician who will decide on need and method of emptying the stomach.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

In case of fire carbon, sulphur and phosphorus oxides can be formed.

- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Do not heat above flash point.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

Information on basic physical and	chemical properties
· General Information · Appearance:	
Form:	Fluid
Color:	Brown
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	>200 °C (>392 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	255 °C (491 °F) (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	<0.1 hPa (20 °C)
· Density at 20 °C (68 °F):	0.872 g/cm³ (7.277 lbs/gal) (ASTM D 4052)
Relative density	Not determined.
· Vapor density	Not determined.

(Contd. on page 6)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 5)

· Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: 115.4 mm²/s @ 40 °C (DIN 51562-1)
Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- $\cdot \textit{Thermal decomposition / conditions to be avoided:} \\$

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 6)

- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR,ADN, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR,ADN, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR,ADN, ADN, IMDG, IATA		
Class	Void	
Packing group		
DOT, ADR,ADN, IMDG, IATA	Void	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex	ll of	
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	Void	

-US

(Contd. on page 8)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 7)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

Gara			
· Section 355 (extremely hazardous substances):			
None of the ingredients is listed.			
· Section 313 (Specific toxic chemical listings):			
122-39-4 d	122-39-4 diphenylamine		
TSCA (Toxic Substances Control Act):			
112-41-4	dodec-1-ene		
26401-35-4	DTDA		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic		
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-diethylbutyl and iso-Pr)esters, zinc salts		

- 70024-69-0 Benzenesulfonic acid, mono-C20-24-alkyl derivs., calcium salts
 36878-20-3 Reaction products of Benzeneamine, N-phenyl- with nonene (branched)
 80939-62-4 Amine, C11-14-verzweigte Alkyl-, Monoexyl und Dihexylphosphate
- 91273-04-0 N,N-bis(2-ethylhexyl)-((1,2,4-triazol-1-yl)methyl)amine 597-82-0 O,O,O-Triphenylthiophosphat
 - 122-39-4 diphenylamine
 - 106-20-7 bis(2-ethylhexyl)amine
 - 288-88-0 1,2,4-triazole
- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

122-39-4 diphenylamine

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · National chemical directories Components listed or exempted from listing:
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: RACING PRO 4T SAE 15W/50

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Abteilung Produktsicherheit
- · Date of preparation / last revision 04/12/2016 / -
- · Abbreviations and acronyms:

Flam. Lig. 4: Flammable liquids - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Repr. 2: Reproductive toxicity – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard - Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3