

Valve Clean

Description

A combination of active agents, specifically developed to clean the intake valves and the combustion chamber of port injected engines. Protects against corrosion in the fuel system.

Properties

- reduces deposits
- reduces residues
- good corrosion protection
- compatible for the use with turbochargers and catalytic converters
- burns ash-free
- environmentally friendly
- economical
- prevents carburetor icing

Technical data

Color / appearance	hellbraun / light brown
Density at 59 °F	0,809 g/ml DIN 51757
Flash point	145 °F DIN ISO 2592
Pour point	< -40 °F DIN ISO 3016
Viscosity at 104 °F	<7 mm ² /s
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

Suitable for use in all 4-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF).

Application

For best results add Valve Clean to gasoline at each filling. Contents (150 mL) is sufficient for 25–75 Liters (7 gal. to 20 gal.) fuel.

Comment

WARNING: Cancer- www.P65Warnings.ca.gov



Available pack sizes

150 ml Can sheet metal	2001 USA (-EN-)
150 ml Can sheet metal	7701 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.