

Top Tec ATF 1600

Description

Fully synthetic automatic transmission fluid, developed for exclusive use in 1st generation Mercedes-Benz 7-speed automatic transmission (up to June 2010) and also compatible with various older Mercedes-Benz 5-speed automatic transmission requirements. Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a red color.

Properties

- excellent corrosion protection
- excellent wear resistance
- prevents foam formation
- excellent viscosity/temperature properties
- very good low-temperature properties
- outstanding resistance to oxidation
- for eliminating shifting problems
- outstanding friction characteristics
- excellent resistance to aging

Specifications and approvals:

MB-Approval 236.14

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.12

Technical data

Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	28,7 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,45 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brook-field)	<= 20000 mPas ASTM D 2983-09
Viscosity index	188 DIN ISO 2909
Flash point	403 °F DIN ISO 2592
Pour point	-49 °F DIN ISO 3016
Color / appearance	rot

Areas of application

For Mercedes-Benz automatic transmissions where a ATF fluid meeting current product specifications is required or recommended.



Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.

Available pack sizes

1 l Can plastic	20024 USA AND CANADA (-EN-F-)
20 l Canister plastic	20026 USA AND CANADA (-EN-F-)
60 l Drum sheet metal	22066 USA AND CANADA (-EN-F-)
205 l Drum sheet metal	22163 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.