

Top Tec ATF 1900

Description

Fully synthetic, low viscosity automatic transmission fluid, developed to meet the strict requirements of 2nd generation Mercedes-Benz 7-speed automatic transmissions (type 722.9). Improved formula for sustained transmission life and maximum transmission shift performance. The fluid is a blue color.

Properties

- reduces fuel consumption
- excellent viscosity/temperature properties
- outstanding friction characteristics
- high efficiency
- very good low-temperature properties

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.15

Technical data

| | |
|----------------------------------|---|
| Density at 59 °F | 0,845 g/cm ³ DIN 51757 |
| Viscosity at 104 °F | 19,0 mm ² /s ASTM D 7042-04 |
| Viscosity at 212°F | 4,4 mm ² /s ASTM D 7042-04 |
| Viscosity at -40 °F (Brookfield) | <= 10000 mPas ASTM D 2983-09 |
| Viscosity index | 148 DIN ISO 2909 |
| Pour point | -60 °F DIN ISO 3016 |
| Flash point | 374 °F DIN ISO 2592 |
| Color / appearance | blaugrün |

Areas of application

For Mercedes-Benz 7-speed automatic transmissions where an ATF fluid meeting current product specification is required or recommended.

Application

Observe the manufacturers instructions! Optimum efficiency and product performance is only possible when the product is used undiluted.



Comment

 **WARNING: Cancer-** www.P65Warnings.ca.gov

Available pack sizes

| | |
|-----------------------|----------------------------------|
| 1 l Can plastic | 20028 USA (-EN-) |
| 1 l Can plastic | 20360 CANADA (-EN-F-) |
| 20 l Canister plastic | 20030 USA AND CANADA (-EN-F-) |

Our information is based on thorough research and may be considered reliable, although not legally binding.