

## Touring High Tech SAE 20W-50

### Description

Mineral based all-season motor oil, particularly suited for older generation high mileage gasoline and diesel vehicles. Provides a stable lubricating film even under extreme operating conditions. Designed with proven wear protection technology. Keeps rubber seals such as valve stem seals, crank seals, cam seals etc. soft and pliable for low oil consumption.

### Properties

- excellent dispersion properties
- tested for the use with catalytic converters
- can be used in gasoline and diesel engines with and without turbocharger
- high lubrication reliability
- prevents oil sludge
- low evaporation loss
- excellent wear resistance
- excellent cleaning effect
- optimum stability to aging
- high shear stability

### Specifications and approvals:

ACEA A3 • ACEA B4 • ACEA E2 • API SL • API CG-4 • Allison C4 • MIL-L 2104 E

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

Caterpillar TO-2 • MAN 271 • MB 228.3

### Technical data

SAE class (engine oils)	20W-50 SAE J300
Density at 59 °F	0,880 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	153 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	18,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -4 °F (MRV)	< 60000 mPas ASTM D4684
Viscosity at 5 °F (CCS)	≤ 9500 mPas ASTM D5293
Viscosity index	132 DIN ISO 2909
HTHS at 302 °F	≥ 3,7 mPas ASTM D5481
Pour point	-22 °F DIN ISO 3016



### Technical data

Evaporation loss (Noack)	7,2 % CEC-L-40-A-93
Flash point	464 °F DIN ISO 2592
Total base number	10,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L5,5 DIN ISO 2049

### Areas of application

For gasoline or diesel engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

### Application

Observe the manufacturers instructions!

### Available pack sizes

5 l Canister plastic	20114 USA AND CANADA (-EN-F-)
205 l Drum sheet metal	22127 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**