

# Product information

## Special Tec V SAE 0W-30

PI 37/25/08/2020



### Description

Fully synthetic superior, low friction motor oil. Developed specifically for use in various late model Volvo vehicles and also suitable for use in several other manufacturers vehicles. The low viscosity ensures excellent cold start behavior, improves engine efficiency and reduces fuel consumption. Use with extended oil change intervals as per manufacturer.

### Properties

- high shear stability
- saves fuel
- compatible for the use with turbochargers and catalytic converters
- optimum stability to aging
- outstanding engine cleanliness
- high lubrication reliability
- instant lubrication after cold start

### Specifications and approvals:

ACEA A5 • ACEA B5 • API SL • API CF • ILSAC GF-3 • Volvo VCC 95200377

### Technical data

|                           |   |
|---------------------------|---|
| SAE class (engine oils)   | 0W-30<br>SAE J300                         |
| Density at 59 °F          | 0,845 g/cm <sup>3</sup><br>DIN 51757      |
| Viscosity at 104 °F       | 51,5 mm <sup>2</sup> /s<br>ASTM D 7042-04 |
| Viscosity at 212°F        | 9,9 mm <sup>2</sup> /s<br>ASTM D 7042-04  |
| Viscosity at -40 °F (MRV) | < 60000 mPas<br>ASTM D 4684               |
| Viscosity at -31 °F (CCS) | ≤ 6200 mPas<br>ASTM D 5293                |
| Viscosity index           | 182<br>DIN ISO 2909                       |
| HTHS at 302 °F            | 2,9 - 3,5 mPas<br>ASTM D 5481             |
| Pour point                | -54 °F<br>DIN ISO 3016                    |
| Evaporation loss (Noack)  | 12,5 %<br>CEC-L-40-A-93                   |
| Flash point               | 439 °F<br>DIN ISO 2592                    |
| Total base number         | 11,1 mg KOH/g<br>DIN ISO 3771             |
| Sulfate ash               | ≤ 1,6 g/100g<br>DIN 51575                 |



### Technical data

|                     |              |
|---------------------|--------------|
| Color number (ASTM) | 3,0          |
|                     | DIN ISO 2049 |

### Areas of application

For gasoline engines where a motor oil according to current specifications is required or recommended. Tested safe with catalytic converters and turbochargers.

### Application

Observe the manufacturers instructions!

### Available pack sizes

|                      |                                  |
|----------------------|----------------------------------|
| 1 l Canister plastic | 20202<br>USA AND CANADA (-EN-F-) |
| 5 l Canister plastic | 20204<br>USA AND CANADA (-EN-F-) |

**Our information is based on thorough research and may be considered reliable, although not legally binding.**