

## Pro-Line Automatic Transmission Cleaner

### Description

A highly effective formulation that removes deposits and debris from inside the transmission before an oil change. Restores proper shifting and overall function while extending transmission life.

### Properties

- gentle and rapid cleaning
- assures optimum shifting performance
- does not attack rubber and plastic seals
- optimizes economical use
- easily dissolves stubborn dirt

### Technical data

Base	Additiv, Naphthenbasisches Spezialöl / additive, naphtha-base special oil
Viscosity index	204
Viscosity at 104 °F	58,0 mm <sup>2</sup> /s
Viscosity at 212°F	11,8 mm <sup>2</sup> /s
Form	flüssig, liquid
Odor	charakteristisch / characteristic
Density at 59 °F	0,885 g/ml

### Areas of application

Suitable for most kind of automatic transmission fluids, ideally suited for use with the LIQUI MOLY Gear Tronic (part no. 7917).

**For professional repair shop use only.**

### Application

Add Pro-Line Automatic Transmission Cleaner to the transmission fluid at operating temperature and let the engine idle for around 10 minutes with the vehicle lifted up. Shift all gears once or twice. Switch off the engine and change oil and filter. For optimum effectiveness we recommend to apply using the LIQUI MOLY Gear Tronic. 300 mL is sufficient for 6-9 Liters (1.6 gal. to 2.4 gal.) ATF.



### Available pack sizes

1 l Can sheet metal

20224

USA AND CANADA (-EN-  
F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**