

Product information

Pro-Line Turbocharger Additive

PI 10/25/08/2020



Description

Provides initial lubrication of new or replaced turbochargers to prevent damage due to oil starvation. Damage to turbocharger may occur within seconds of engine start if not lubricated properly. Pro-Line Turbocharger additive will provide needed protection and allow proper break-in of new units which prevents additional repairs.

Properties

- outstanding break-in protection
- protects against damage caused by lack of oil in the running-in phase
- mixable with most engine oils
- increases operational reliability

Technical data

Color / appearance	dunkelgrau - schwarz / dark grey - black
Solids content	~ 10 %
Viscosity at 68 °F	304,31 mPas DIN 51398
Flash point	> 212 °F DIN ISO 2592
Pour point	5 °F DIN ISO 3016
Thermal stability	> 752 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Density at 68 °F	1,0013 g/cm ³

Areas of application

For all 4-stroke gasoline and diesel engines. Miscible with most commercially available motor oils. Safe for use with catalytic converters and particulate filters (GPF/DPF).

Application

The oil intake passage of the turbocharger is filled to the brim with Pro-Line Turbocharger Additive before the oil supply line is connected.



Available pack sizes

20 g Tube plastic	22074
	USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.