

Scratch Stop

Description

A silicone free polishing paste suitable for universal use. The product can be used to remove scratches, overspray, swirl marks and uneven finish on solid or metallic paintwork. It is also suitable for matt plastic parts as well as polycarbonate headlight lenses, and can be applied either manually or with a buffer.

Properties

- prepares paint surface
- easy removal of weathered paint layers
- silicone-free
- simple to use

Technical data

Odor	charakteristisch / characteristic
Form	pastös, flüssig / pastelike, liquid
Flash point	>142 °F
Density at 68 °F	1,08 g/ml
pH value	7,8
Color / appearance	rosa / rose
Base	Schleifmittel, Wachse / Abrasives, wax
Viscosity at 68 °F	20000-25000 mPas
Shelf life in original sealed container	30 months

Areas of application

Specially developed product for the removal of scratches. Suitable for colored and metallic paints. Ideally suited for treating dulled plastic windows or headlights made of polycarbonate.

Application

Wash the vehicle thoroughly before application. Shake well before use. Use a cloth or sponge to apply and work into the affected area while using light pressure (polish with a foam buffing machine at 1,500 to 2,000 rpm). **Use caution near body panel edges, as the product is abrasive.** Wipe off any polish residue using a clean cloth (preferably a microfibre cloth).



Available pack sizes

200 ml Tube plastic

20384

USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.