



SPECIFIC LL-01 FE

5W-30



BMW Gasoline and Diesel engine oil

Approved BMW Long Life-01 FE

100% Synthetic

TYPE OF USE

100% Synthetic High Performance "Fuel Economy" Lubricant, specially designed for BMW and MINI vehicles, fitted with Gasoline engines meeting Euro 4, 5 and 6 emission standards, requiring a "FE – Fuel Economy" engine oil type and approved BMW Long-Life 01 FE.

Suitable for all types of fuels, Gasoline, leaded or unleaded, Ethanol, LPG, Diesel and biofuels. Compatible with catalytic converters.

Some engines may not be able use this type of oil, before use always check the owner's manual.

PERFORMANCES

STANDARDS ACEA A5 / B5

APPROVALS BMW Long Life-01 FE

The BMW Long Life-01 FE specification imposes severe constraints to the lubricant particularly due to the Valvetronic system. It covers some BMW engines from 2001 and some engines from 2004. BMW LL-01 FE norm covers also all former BMW specifications such as BMW LL-98.

The BMW LL-01 FE standard covers some Gasoline engines running only outside European Union countries, Switzerland, Norway and Liechtenstein. Refer to BMW recommendations when in doubt.

MOTUL Specific LL-01 FE 5W-30 fulfills all the specifications of BMW Long Life-01 FE standard from the BMW Group for BMW, MINI and ROLLS-ROYCE vehicles with no exceptions i.e. for models before and after 2019. For models up to 2019, i.e. until end of 2018 only, MOTUL 8100 X-cess 5W-40 can also be used.

For BMW vehicles requiring an approved BMW LL-04 lubricant, use only products such as MOTUL 8100 X-clean+ 5W-30, MOTUL 8100 X-clean EFE 5W-30, MOTUL 8100 X-clean gen2 5W-40 or MOTUL Specific LL-04 5W-40.

MOTUL SPECIFIC LL-01 FE 5W-30 is particularly resistant at high temperatures to allow better control of oil consumption and to reduce wear thanks to its excellent lubricating properties, while providing significant fuel economy. Provides excellent oil flow, instant oil pressure, faster engine revs-up and faster engine warm-up.

This type of lubricant helps reduce fuel consumption thus reducing greenhouse gas (CO₂) emissions to protect the environment.

This product can also be recommended for when a BMW LL-01 FE 0W-30 lubricant is required.

RECOMMENDATION

Drain interval: refer to manufacturers' recommendations and tune to your own use.

Avoid mixing with lubricants not BMW LL-01 FE compliant.

Before use always refer to the owner manual or handbook of the vehicle.

PROPERTIES

Viscosity grade	SAE J 300	5W-30
Density at 20°C (68°F)	ASTM D1298	0.855
Viscosity at 40°C (104°F)	ASTM D445	63.5 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	10.7 mm ² /s
Viscosity HTHS at 150°C (302°F)	ASTM D4741	3.4 mPa.s
Viscosity index	ASTM D2270	160
Pour point	ASTM D97	-42°C / -44°F
Flash point	ASTM D92	228°C / 442°F
Sulfated ash	ASTM D874	1.45% weight
TBN	ASTM D2896	11.1 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 - FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

09/20