MOTUL

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : 300V² 4T FACTORY LINE 10W50 Product code : 13130

1.2. Relevant identified uses of the substance or mixture and uses advised against

4-stroke engine lubricant

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: . Email : motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

Other emergency numbers

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 1 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336 Ireland : +353 1 8092566 UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235

239671

24 hours a day, 7 days a week

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site. This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

No labelling requirements for this mixture.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 72623-87-1	GHS08	L	25 <= x % < 50
EC: 276-738-4	Dgr		
REACH: 01-2119474889-13	Asp. Tox. 1, H304		
LUBRICATING OILS (PETROLEUM),			
C20-50, HYDROTREATED NEUTRAL			
OIL-BASED			
EC: 939-894-0	GHS08		25 <= x % < 50
REACH: 01-2120031429-59-0000	Dgr		
	Asp. Tox. 1, H304		
PARTIALLY HYDROGENATED			
-3,7,11-TRIMETHYLDODECA-1,3,6,1			
0-TETRAENE, REACTION PRODUCTS			
WITH LINEAR C8-C16 ALPHA			
OLEFIN, HYDROGENATED.			

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) 300V² 4T FACTORY LINE 10W50 - 13130

CAS: 64742-54-7	GHS08	L	2.5 <= x % < 10
EC: 265-157-1	Dgr		
REACH: 01-2119484627-25	Asp. Tox. 1, H304		
DISTILLATES (PETROLEUM),			
HYDROTREATED HEAVY PARAFFINIC			
BASEOIL - UNSPECIFIED			
EC: 253-249-4			1 <= x % < 2.5
REACH: 01-2119488911-28	Aquatic Chronic 4, H413		
BIS(NONYLPHENYL)AMINE			

Information on ingredients :

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8. Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) 300V² 4T FACTORY LINE 10W50 - 13130

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Avoid contact with eyes.

No special precaution apart from the observance of hygiene rules

Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between $5^{\circ}C$ and $40^{\circ}C$ in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

BIS(NONYLPHENYL)AMINE

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Final use:

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method:

Workers.

Dermal contact. Long term systemic effects. 0.62 mg/kg de poids corporel/jour

Inhalation. Long term systemic effects. 4.37 mg de substance/m3

Consumers. Ingestion. Long term systemic effects. 0.31 mg/kg de poids corporel/jour

Dermal contact. Long term systemic effects. 0.31 mg/kg de poids corporel/jour

Inhalation.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) 300V² 4T FACTORY LINE 10W50 - 13130

	Potential health effects:	Long term systemic effects.
	DNEL :	1.09 mg de substance/m3
	LUBRICATING OILS (PETROLEUM), C20-50, HYDRO	TREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)
	Final use:	Workers.
	Exposure method:	Inhalation.
	Potential health effects:	Long term local effects.
	DNEL :	5.4 mg de substance/m3
	Final use:	Consumers.
	Exposure method:	Inhalation.
	Potential health effects:	Long term local effects.
	DNEL :	1.2 mg de substance/m3
Р	redicted no effect concentration (PNEC):	
	BIS(NONYLPHENYL)AMINE	
	Environmental compartment:	Soil.
	PNEC :	26300 mg/kg
	Environmental compartment:	Fresh water.
	PNEC :	0.1 mg/l
	Environmental compartment:	Sea water.
	PNEC :	0.01 mg/l
	Environmental compartment:	Fresh water sediment.
	PNEC :	132000 mg/kg
	Environmental compartment:	Marine sediment.
	DNEO	10000 "

PNEC :

13200 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction. Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) 300V² 4T FACTORY LINE 10W50 - 13130

Color:	Amber	
Important health, safety and environmental information		
pH :	Not relevant.	
Flash Point Interval :	FP > 100°C.	
Vapour pressure (50°C) :	Not relevant.	
Density :	< 1	
Water solubility :	Insoluble.	
Viscosity :	107.5 mm²/s à 40°C	

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

10.5. Incompatible materials

Strong oxidants

Acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

BIS(NONYLPHENYL)AMINE Oral route :

LD50 > 5000 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route :

Dermal route :

2,000 < LD50 <= 5000 mg/kg Species : Rat OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC BASEOIL - UNSPECIFIED (CAS: 64742-54-7) Oral route : LD50 > 5000 mg/kg

Species : Rat

LD50 > 5000 mg/kg Species : Rabbit

Inhalation route (Dusts/mist) :

LC50 <= 5 mg/l

Specific target organ systemic toxicity - repeated exposure :

PARTIALLY HYDROGENATED -3,7,11-TRIMETHYLDODECA-1,3,6,10-TETRAENE, REACTION PRODUCTS WITH LINEAR C8-C16 ALPHA OLEFIN, HYDROGENATED. Oral route : C = 300 mg/kg poids corporel/jour

C = 300 mg/kg poids corporel/jour Species : Rat Duration of exposure : 90 jours

Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

Aspiration hazard :

 \bigcirc

6

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 80-62-6 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

2.1. Toxicity	
2.1.1. Substances	
	YLDODECA-1,3,6,10-TETRAENE, REACTION PRODUCTS WITH LINEAR C8-C16 ALPHA OLE
Fish toxicity :	LC50 > 100 mg/l Duration of exposure : 96 h
	NOEC > 100 mg/l
	Duration of exposure : 14 jours
Crustacean toxicity :	EC50 > 100 mg/l
	Duration of exposure : 48 h
	NOEC = 100 mg/l
	Duration of exposure : 21 jours
Algae toxicity :	ECr50 > 100 mg/l
	Duration of exposure : 72 h
BIS(NONYLPHENYL)AMINE	
Fish toxicity :	LC50 > 100 mg/l
	Species : Danio rerio
	Duration of exposure : 96 h
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 > 100 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
Algae toxicity :	ECr50 > 100 mg/l
	Species : Desmodesmus subspicatus
	Duration of exposure : 72 h
	OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
DISTILLATES (PETROLEUM), HYDROTREATED BASEOIL - UNSPECIFIED (CAS: 64742-54-7)	HEAVY PARAFFINIC
Fish toxicity :	LC50 > 100 mg/l
-	Species : Pimephales promelas
	Duration of exposure : 96 h
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 = 1000 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
	NOEC = 10 mg/l
	Species : Daphnia magna

AFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version 2.2 (30-10-2019) - Page 7/9	
00V ² 4T FACTORY LINE 10W50 - 13130	
	Duration of exposure : 21 jours OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)
Algae toxicity :	ECr50 > 100 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 72 h
	OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
	NOEC = 100 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
12.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
12.2. Persistence and degradability	
12.2.1. Substances	
BIS(NONYLPHENYL)AMINE	
Biodegradability :	no degradability data is available, the substance is considered as not
	degrading quickly.
DISTILLATES (PETROLEUM), HYDROTREATED H	EAVY PARAFFINIC
BASEOIL - UNSPECIFIED (CAS: 64742-54-7)	
Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
PARTIALLY HYDROGENATED -3,7,11-TRIMETHYI HYDROGENATED.	LDODECA-1,3,6,10-TETRAENE, REACTION PRODUCTS WITH LINEAR C8-C16 ALPHA OLEF
Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
12.3. Bioaccumulative potential	
No data available.	
12.4. Mobility in soil	
Not very mobile in soil.	
The product is insoluble in water and will spread on the	ie surface
12.5. Results of PBT and vPvB assessment	
No data available.	
12.6. Other adverse effects	
Do not dispose of the product in the natural environm	ent, effluents or surface waters.
German regulations concerning the classification of	f hazards for water (WGK, AwSV vom 18/04/2017, KBws) :
WGK 3 : Extremely hazardous for water.	
ECTION 13 : DISPOSAL CONSIDERATIONS	
	ontainer must be determined in accordance with Directive 2008/98/EC.
13.1. Waste treatment methods	
Do not pour into drains or waterways.	
Waste :	a human haalth without harming the anvironment and in particular without risk to water air
soil, plants or animals.	ng human health, without harming the environment and, in particular without risk to water, air,
Recycle or dispose of waste in compliance with curre Do not contaminate the ground or water with waste, or	nt legislation, preferably via a certified collector or company. Io not dispose of waste into the environment.

Soiled packaging :

2

2

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- -
- 14.5. Environmental hazards
- 14.6. Special precautions for user

SECTION 15 : REGULATORY INFORMATION


15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2: The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)
- Container information:
 - No data available.
- Particular provisions :

No data available.

- German regulations concerning the classification of hazards for water (WGK, AwSV vom 18/04/2017, KBws) : WGK 3 : Extremely hazardous for water.
 - Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) : NFPA 704, Labelling: Health=0 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



15.2. Chemical safety assessment

Product is not classified health and environmental hazard. Exposure scenarios are not required.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Abbreviations :

- DNEL : Derived No-Effect Level
- PNEC : Predicted No-Effect Concentration
- ADR : European agreement concerning the international carriage of dangerous goods by Road.
- IMDG : International Maritime Dangerous Goods.
- IATA : International Air Transport Association.
- ICAO : International Civil Aviation Organisation
- RID : Regulations concerning the International carriage of Dangerous goods by rail.
- WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic. vPvB : Very persistent, very bioaccumulable. SVHC : Substances of very high concern.