



CLASSIC SAE 30

**4 Stroke Engine Oil
Engineered for Classic Vehicles**

Premium Mineral Monograde

APPLICATION

Premium Mineral monograde engine oil engineered for Classic Gasoline or Diesel 4 Stroke engines and gearboxes built before 1950.

Specially designed for Ancestor, Veteran, Vintage, Prewar and Classic vehicles requiring, a SAE 30 viscosity grade lubricant.

Modern version of classic monograde engine oil to perfectly suit requirement of climate conditions.

Easier start-ups for vehicles that are stored for long period of time.

Can also be used as a **break-in oil**.

FEATURES AND BENEFITS

MOTUL CLASSIC SAE 30 is a modern technology lubricant specially developed for vintage engines, design and formulated with a **High Zinc, Phosphorus level (ZDDP content > 1800 ppm)** to provide the best anti-wear protection for your classic engine (genuine or rebuilt). High ZDDP levels offer supreme protection of critical components like high-lift, flat-tappet cams, prone to wear because of the high friction developed in these parts.

Premium Mineral monograde lubricant with very low detergent level in order to be harmless to cork, paper, felt and fabric gaskets from that period.

Compatible with "yellow" nonferrous metals as brass, bronze and copper, which makes it ideal for classic gearboxes.

Its excellent cold flow properties prevent engine wear during start-ups, even after long periods of storage. Highly adhesive, its rust inhibitors and anticorrosion additives provide extra protection during wintering periods.

Can be used as break-in oil if drain intervals are shortened.

RECOMMENDATIONS

Drain interval: drain at least once a year and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 300	30
Density at 20°C (68°F)	ASTM D1298	0.891
Viscosity at 40°C (104°F)	ASTM D445	103.8 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	11.5 mm ² /s
Viscosity index	ASTM D2270	97
Pour point	ASTM D97	-30°C / -22°F
Flash point	ASTM D92	254°C / 489°F
TBN	ASTM D2896	1.8 mg KOH/g

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Boulevard Félix Faure - 93303 Aubervilliers Cedex - BP 94 - FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

01/21