

MOTYLGEAR 80W-140

**Lubricant for heavily loaded transmissions
Technosynthese®**

TYPE OF USE

All mechanical transmission synchronized or not synchronized gearboxes, gearbox/differential, transfer gearbox and hyoid differentials without limited slip system operating under shocks, heavy loads and low revolution speed or moderate loads and high revolution speed.

Specially recommended when the xxW-90 lubricant requested by the gearbox manufacturer is not strong enough to handle very heavy loads, shocks or/and high temperatures.

PERFORMANCES

STANDARDS API GL-4 / GL-5
 MIL-L -2105 D

Extreme Pressure lubricant for an efficient anti wear protection reinforced with Technosynthese® synthetic base stocks for a better resistance at high temperature and life time.

Stays in 140 grade after KRL 20 hours shear test as requested by SAE J306 Standard, July 1998 update.

Very high lubricating power which decreases friction and wear.

High viscosity at hot temperature for a higher oil film resistance in extreme operation conditions: heavy loads, shocks, high temperatures.

Oil film stability at high temperature.

Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to manufacturers' requirements and adjust according to your own use.

PROPERTIES

| | | |
|-----------------|-----------|---------|
| Viscosity grade | SAE J 300 | 80W-140 |
|-----------------|-----------|---------|

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com



MOTYLGEAR 80W-140

Lubricant for heavily loaded transmissions
Technosynthese®

| | | |
|----------------------------|------------|--------------------------|
| Density at 20°C (68°F) | ASTM D1298 | 0.897 |
| Viscosity at 40°C (104°F) | ASTM D445 | 289.7 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 40.0 mm ² /s |
| Viscosity Index | ASTM D2270 | 192.0 |
| Pour point | ASTM D97 | -27.0 °C / -16.0 °F |
| Flash point | ASTM D92 | 200.0 °C / 392.0 °F |