



RED LINE POWER STEERING FLUID



- Improved wear protection, resists thermal breakdown, evaporation and foaming
- Provides continued high pump output, suitable for most power steering units
- Lightweight fluid avoids power loss
- 50% greater high-temp viscosity and 1/5 of the high-temp evaporation
- Greater heat resistance helps to prevent boil-over
- Helps to prevent high-temp steering fade and difficult effort steering at low temps
- Compatible with petroleum's and synthetics
- 1/4 of the oxidation of petroleum power steering fluids
- Helps prevent leakage and squealing

TYPICAL PROPERTIES:

Rust (D66A/B)	Pass
Vis @ 100°C after shear	6.47 cSt
Foam	0
Fire Point °C	258
Copper Corrosion	1b
Vis @ -40°C	5,400 cP
Vis @ 100°C	7.0 cSt
Vis @ 40°C	31 cSt
Viscosity Index	199
Pour Point, °C	-50
Pour Point, °F	-58

PACKAGE SIZES:

- 30404 - Power Steering Fluid - quart
- 30406 - Power Steering Fluid - 5 gallon

ADDITIONAL INFORMATION

RED LINE POWER STEERING FLUID satisfies the service fill requirements of most auto manufacturers and can be used where the manufacturer calls for any automatic transmission fluid such as Dexron®, Dexron II®, II-E®, or Dexron III®, Ford Type-F, Mercon or M2C138-CJ such as required by Ford, AMC, Toyota, Nissan, Lexus, Infiniti, Jaguar, VW, Mercedes-Benz, BMW, SAAB, Subaru, Volvo, Porsche, Mitsubishi, Mazda and many others.

This fluid also satisfies power steering units requiring GM PN 1050017 or 1052884 (Spec Number 9985010), Chrysler Spec Number 5931, and Ford Spec Number M2C33-F. It also satisfies the hydraulic specifications of Denison HF-O, Vickers vane pumps and Sundstrand piston pumps.

Suitable replacement for Eaton Supercharger fluid, GM pt# 12345982, AC Delco pt# 10-4041, Ford pt# XL-4, Ford ESE-M99C115-A, Toyota pt# 08885-80108

For health safety information, please refer to the [Safety Data Sheet](#) at REDLINEOIL.COM